

April 14, 2006



U.S. Department  
of Transportation

400 Seventh Street, S.W.  
Washington, D.C. 20590

**Pipeline and  
Hazardous Materials  
Safety Administration**

DOT-SP 6611  
(NINTH REVISION)

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: (See individual authorization letter)
2. PURPOSE AND LIMITATION:
  - a. This special permit authorizes the use of non-DOT specification portable tanks for the transportation in commerce of certain nonflammable cryogenic liquids. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
  - c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 172.203 and 173.318 in that non-DOT specification portable tanks are not authorized, except as specified herein.
5. BASIS: This special permit is based on the application of Air Products and Chemicals, Inc. dated March 15, 2006, submitted in accordance with § 107.109.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Helium, refrigerated liquid ( <i>cryogenic liquid</i> )	2.2	UN1963	N/A

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Prescribed packaging is a non-DOT specification portable tank designed and constructed in accordance with Section VIII of the ASME Code and subparagraphs b. or c. of this paragraph. The portable tank is skid-mounted or enclosed in an ISO type frame. The portable tank is vacuum-insulated with a supplemental liquid nitrogen shield. Design pressure is 115 psig for the internal tank, and 6 psig for the liquid nitrogen tank. Design temperature is -452°F., for the inner tank and any part, valve or fitting that may come in contact with the lading; and -320°F., for the liquid nitrogen tank and any part, valve or fitting that may come in contact with liquid nitrogen. Water capacity is 5,000 gallons for the inner tank. Inner and nitrogen tank material is SA 240 Type 304 or 3041 stainless steel. Jacket material is SA 36, (ASTM) A 283 or equivalent steel.

b. Each portable tank must conform to Gardner Cryogenics' drawing 6510A, design calculation #1190 and supplemental data and calculations furnished with Gardner Cryogenics' letter dated December 21, 1973, on file with the Office of Hazardous Materials Special Permits and Approvals (OHMSPA). No new construction is authorized unless the portable tank design conforms with paragraph 7.c. of this special permit.

c. New construction after December 31, 1991, must conform with § 178.338, except as follows: Corresponding drawings and calculations must be submitted to the OHMSPA prior to first shipment of a new tank design.

- (1) Impact testing is not required for Type 304 or 3041 stainless steel.

(2) Section 178.338-10 does not apply.

(3) The portable tank need not conform with § 178.338-13(a) or (b). Lifting lugs, framework and any anchoring to the inner tank, the nitrogen shield tank or tank jacket must conform with § 178.338-13(a). A portable tank that meets the definition of "container" must meet the requirements of 49 CFR Parts 450 through 453 and each tank design must be qualified in accordance with § 178.270-13(c).

(4) Effective August 1, 2002, "DOT-SP 6611" must replace the mark "MC 338".

d. Each portable tank must be equipped with pressure relief devices conforming with § 173.318 as applicable for the lading. Tanks made before March 2, 1977, may be equipped with pressure relief devices having a relief capacity of 3030 SCFM.

8. SPECIAL PROVISIONS:

a. Each portable tank must be reinspected and retested once ever five years in accordance with § 180.605 as prescribed for DOT Specification 51 portable tanks. The test pressure of the inner tank must be determined from the following formulas:

If there is no vacuum in the outer jacket during the test:

$$P_T = 1.25 \times [P_d + H^s + 14.7]$$

If vacuum exists in the outer jacket during test:

$$P_T = 1.25 \times [P_d + H_s + 14.7] - 14.7$$

Where:

$P_T$  = Test pressure (psig)

$P_d$  = Design pressure (maximum allowable working pressure) (psig)

**April 14, 2006**

$H_s$  = Static head of liquid in inner tank (psig)

b. Each portable tank must be plainly marked on both sides near the middle, in letters at least two (2) inches high on a contrasting background, "DOT-SP 6611".

c. Each portable tank must be prepared and shipped as required in § 173.318, as applicable for the lading.

d. Shipments by cargo vessel must conform with the following:

(1) The package must conform with § 176.76(h). Portable tanks may be overstowed only if enclosed in ISO-type frames and otherwise suitably protected. In all situations, the portable tanks must be stowed such that they are readily accessible and can be monitored in accordance with the provisions of this special permit.

(2) The legend "One Way Travel Time \_\_\_\_\_ Hours" (OWTT) must be marked on the shipping paper and on the dangerous cargo manifest immediately after the container description. The OWTT is determined by the formula:

$$\text{OWTT} = \text{MRHT} - 24 \text{ hours.}$$

(3) A written record of the portable tank's pressure and ambient (outside) temperature at the following times must be prepared for each shipment:

- (i) At the start of each trip;
- (ii) Immediately before and after any manual venting;
- (iii) At least once every 24 hours; and
- (iv) At the destination point.

(4) Any lading road relief (pressure control) valve (PCV) set at a pressure lower than that prescribed for the (safety) pressure relief valve must be closed,

**April 14, 2006**

unless the OWTT is determined based on the setting of the PCV.

- e. No person may transport a charged portable tank unless the pressure of the lading is equal to or less than that used to determine the marked rated holding time and the OWTT is equal to or greater than the elapsed time between the start and termination of travel.
  - f. The actual holding time for each tank must be determined after each shipment. If it is determined that the actual holding time is less than 90 percent of the MRHT of the tank, the tank may not be refilled until it is restored to its MRHT or the tank is remarked with the reduced holding time determined by this examination.
  - g. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the package or its contents and it is reoffered for transportation in conformance with this special permit and the HMR.
  - h. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.
  - i. Packages permanently marked 'DOT-E 6611', prior to October 1, 2007 may continue to be used under this special permit for the remaining service life the package or until the special permit is no longer valid. Packages marked on or after October 1, 2007 must be marked 'DOT-SP 6611'.
9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle and cargo vessel.
10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel and motor vehicle used to transport packages covered by this special permit.

**April 14, 2006**

11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:

- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
- o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
- o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.


Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term 'exemption' to 'special permit' and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of

**April 14, 2006**

this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for Robert A. McGuire  
Associate Administrator  
for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at [http://hazmat.dot.gov/sp\\_app/special\\_permits/spec\\_perm\\_index.htm](http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm) Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: Olson/sln/kah